

Data sheet

metabo®

Angle grinder - Metabo WE 15-125 Quick, 110 Volt

- Highest service life for extreme applications: robust, powerful angle grinder with greatest power density in its class for quick work progress
- New, patent-pending Metabo Marathon motor with up to 50% more torque and up to 20% higher overload capacity for quicker material removal and longer service life
- Tacho-Constamatic (TC)-Full Wave Electronics: fast work progress by means of constant speed under load
- Now even faster: M-Quick System for tool-free disc change at the touch of a button by means of M-Quick flange nut
- Tool-free adjustable guard; twist-proof
- Side handle Metabo VibraTech (MVT) handle vibration damping for convenient continuous operation
- Metabo S-automatic Torque Limiting Clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user protection and swift progress
- Electronic overload protection, soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor
- Cable length 4 meter



Comes with:

- Guard
- Inner support flange
- M-Quick flange nut
- Side handle

Article-number	Model	Voltage Volt	Rated input power Watt	No-load speed /min	Torque Nm	Grinding wheel mm	Revolution at rated load /min	Spindle thread	Weight kg
1398098	WE 15-125 Quick	110	1 550	11 000	3,5	125	11 000	M14	2,5*

*Weight without power cable



Vibration	
Surface grinding	6 m/s ²
Uncertainty of measurement K	1,5 m/s ²
Grinding with sandpaper	3,6 m/s ²
Uncertainty of measurement K	1,5 m/s ²
Noise emission	
Sound pressure level	93 dB(A)
Sound power level (LwA)	104 dB(A)
Uncertainty of measurement K	3 dB(A)