



CRC GASKET REMOVER
(Non- Chlorinated)
Ref. : 10471

1. GENERAL DESCRIPTION

Gaskets and adhesives stripper.

CRC Gasket Remover is a blend of non-chlorinated powerful solvents, formulated for the easy removal of gasket cement, adhesives and sealants. It helps to protect equipment surfaces by eliminating damage caused by excessive scraping.

2. FEATURES

- High penetrating power.
- Controlled evaporation.
- Clings to vertical surfaces, ideal for fixed industrial equipment.
- Softens and eases removal of conventional and formed in-place gaskets, gasket cements and sealants.
- Loosens carbon deposits.
- Dissolves tar, greases, dried oils, adhesives, resinous deposits, etc.
- Avoids accidental and costly damage caused by excessive scraping.

3. APPLICATIONS

Removal of:

- Gasket residues on :
 - cylinder heads
 - crankcases
 - gearboxes
 - water pump flanges, ...
- Carbon deposits on :
 - valve seats
 - cylinder heads
 - metal engine components, ...
- Mastics
- Putties
- Sealants
- Adhesives



Manufactured by :
CRC Industries Europe BVBA
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com





CRC GASKET REMOVER
(Non- Chlorinated)

Ref. : 10471

4. DIRECTIONS

- Mask painted surfaces from over spray. Wear eye protection and non-porous (nitril rubber) gloves.
- Shake well or stir before application and apply a thick film on area to be treated.
- Allow product to work for 10-20 minutes. Remove residues with a rag, stiff bristled brush or putty knife. Repeat application if necessary.
- Clean treated surface with a solvent cleaner (CRC Quickleen) to remove waxy product film.
- Test before use on plastics or rubber. Do not use on energised equipment.

A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.

5. TYPICAL PRODUCT DATA (without propellant)

Appearance	: viscous opaque liquid
Specific gravity @ 20°C	: 0,92
Boiling range (solvents)	: 40-200°C
Freezing point	: < -20°C
Flash point (closed cup)	: < -0°C
pH	: neutral
Viscosity	: 700-1500 mPa.s (thixotropic)
Kauri-Butanol value (solvents)	: > 120
Vapour density (solvents, vs. air = 1)	: > 2
Non-volatile content	: 1,5% wt

6. PACKAGING

aerosol : 12 x 300 ml

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 10471 03 0197 03

Date : 18 June 2008



Manufactured by :
CRC Industries Europe BVBA
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com

