



## CRC HD VASELINE

Ref. : 10835

### 1. GENERAL DESCRIPTION

---

**HD Vaseline** is based on pure white Vaseline, a paraffin oil that hardens to a pasty consistency at room temperature. Pure Vaseline is compatible with most materials. The high level of purity has been proven beneficial when used as a lubricant or to give corrosion protection in electro technology.

### 2. FEATURES

---

- After evaporation of the solvent, a thick pasty protective film is left.
- Water repellent.
- Protects contacts in heavy-duty conditions against future corrosion.
- Lubricates heavy-duty contacts and sliding or spring-loaded contacts, hence preventing wear.
- Convenient 360° (upside-down) spray valve for aerosols.

### 3. APPLICATIONS

---

- Battery clamps in the automotive sector.
- Push-pull connectors used outdoor and in unprotected environment on cars, trucks and trailers.
- End of line switches on trucks, trailers, forklifts, cranes and agricultural equipment.
- Spring loaded contacts on sliding doors and third/fifth doors in cars.

### 4. DIRECTIONS

---

- Spray a layer of about 1 mm thick on clean contacts.
- Allow the solvents to evaporate before energizing.
- A safety data sheet (MSDS) according EU93/112 is available for all CRC products.
- Do not use on energized equipment.

### 5. TYPICAL PRODUCT DATA (without propellant)

---

Flash point	(ASTM D 56)	:	< 0°C
Specific gravity	@ 20°C (FEA 605)	:	0,727 g/cm <sup>3</sup>
Appearance		:	opaque white

### 6. PACKAGING

---

Aerosol : 6 x 200 ml

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com).

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 10835 03 1201 01  
Date : 23 september 2003



Manufactured by :  
CRC Industries Europe NV  
Touwslagerstraat 1 – 9240 Zele – Belgium  
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34  
[www.crcind.com](http://www.crcind.com)

