



[+ View More](#)

PRODUCT NUMBER: 1005324

## ME86 - Manyard Shock absorbing Lanyard - 1.5m - ML00+ML04

Complete 1,5m with 1 galvanised connector and 1 snap hook 63mm.



Overview

### Reference Number

1005324

### Product Type

Fall Protection

### Range

Shock Absorbing Lanyards

### Brand

Miller by Honeywell

### Industry

• Industry • Building and Construction

### Product Use

**1.5m Shock absorbing Lanyard - complete with 1 screwgate karabiner (ML00) & Automatic Snap hook, with TEFLON finish**

Added elasticity 32%

Integrated shock absorber

Highly resistant external webbing, Teflon finish

Warning flag

1 Screw karabiner and 1 Automatic Scaff hook

Security Clip

### Feature

## Features & Benefits

A unique stretchable design. A safety clip that straps on to the harness to hold the Manyard when not in use. Special woven shock-absorbing inner core. Heavy tubular outer jacket. Unique warning flag which provides visual proof that a lanyard has been involved in a fall and should be removed from service. Reliable visual inspection: the integral res core becomes visible if the outer jacket is damaged or worn. The TEFLON hi-tech protective finish on the outer tubular jacket prolongs the service life of the Manyard.

### Benefit

Lightweight and easy to use, the elasticated manyard is ideal for maintenance on cranes or granties. When contracted the elasticated shock-absorbing lanyard reduces the risk of tripping or snagging. The unique woven shock-absorbing material reduces fall arrest forces.

## Technical Description

### Length

1,5m

### Weight

0.920 Kg

### Breaking Strength

> 15 KN

### Operating Temperature

-30°C to +50°C

## Webbing

### Webbing Raw Material

Polyamide

### Webbing Breaking Strength

>2200 daN

## Connector

### Connector Type

TypeSnap hook

### Connector Raw Material

Raw MaterialWhite chromate steel

### Connector Opening

Opening 65 mm

### Connector Breaking Strength

Breaking Strength> 2200 daN

### Connector Standard

StandardEN 362

## Connector

### Connector Type

TypeCS20

### Connector Raw Material

Raw MaterialZinc-plated steel

### Connector Opening

Opening18 mm

### Connector Breaking Strength

Breaking Strength> 2500 daN

**Connector Standard**

StandardEN 362

**Energy Absorber**

**Energy Absorber Raw Material**

Polyester fibers

**Energy Absorber Breaking Strength**

> 500 daN

**Complementary Information**

Elasticity 30.0 % Length Folded 1.05m External highly resistant webbing Polyamide webbing 45mm - green Teflon finish Breaking strength: > 2500 daN

Certifications

 **E.C. Declaration of Conformity**

**EC Category PPE**

3

**Quality Assurance**

ISO 9001 / 2000

**EC Certificate Number**

333

**EC Attestation**

 EC Attestation

**EC Attestation Number**

0082/490/160/04/01/0089 EXT N°01/10/08

We're sorry, there are no images available at this time.

Additional Information

**User Manual**

NT90004208 IND L

**User Information Sheet**

User manual

Packaging

**EAN Code**

7312550053188

© Honeywell International Inc.